


COIL FORMER


General data 8-pins EE16/8/7 coil former

| PARAMETER | SPECIFICATION |
|-------------------------------|---|
| Coil former material | phenolformaldehyde (PF), glass-reinforced, flame retardant in accordance with "UL 94V-0"; UL file number E59481 |
| Pin material | copper-tin alloy (CuSn), tin (Sn) plated |
| Maximum operating temperature | 180°C, "IEC 60085", class H |
| Resistance to soldering heat | "IEC 60068-2-20", Part 2, Test Tb, method 1B, 350 °C, 3.5 s |
| Soldeerability | "IEC 60068-2-20", Part 2, Test Ta, method 1 |









Winding data and area product for 8-pins EE16/8/7 coil former

| NUMBER OF SECTIONS | WINDING AREA (mm²) | MINIMUM WINDING WIDTH (mm) | AVERAGE LENGTH OF TURN (mm) | AREA PRODUCT Ae x Aw (mm ⁴) | TYPE NUMBER |
|-----------------------|--------------------------|-------------------------------------|--------------------------------------|--|---------------|
| 1 | 27 | 8.80 | 41 | 730 | EE-1611-1S-8P |

 $\begin{tabular}{lll} Tolerances unless otherwise specified: \\ 0<L\leq 4\pm 0.10 & 4<L\leq 16\pm 0.20 \\ 16<L\leq 45\pm 0.30 & 45\leq L\pm 0.40 \\ Pin Dim: \pm 0.05 & Thickness: \pm 0.20 & Pin Pitch: \pm 0.20 \\ \end{tabular}$

| Di | Dimensions: (mm) | REMARK | | |
|----|---------------------|------------|----------|-----------------------------------|
| | (11111) | Mould No.: | | Bobbin material: T378J |
| | | Code No.: | FAY01216 | Available for Fuan core: EE16/8/7 |
| | | | | |



Fuan Electronics

TEL :0086-514-87693589 EML :sales@fuantronics.net WEB:www.fuantronics.net

| Make: P.Xiao | Material Number: A40163800058 | |
|-----------------------|-----------------------------------|--|
| Checked: Beson. zhan | Document/Rev: 00 | |
| Approved: Anson. zhan | Date of Recognition: Dec./02/2019 | |