PARAMETER		SPECIFICATION			
Coil former material		phenolformaldehyde (PF), glass-reinforced, flame retardant in accordance with "UL 94V-0"; UL file number E59481			
Pin material		copper-tin alloy (CuSn), tin (Sn) plated			
Maximum opera	ating temperature	180°C, "IEC 60085", class H			
Resistance to soldering heat		"IEC 60068-2-20", Part 2, Test Tb, method 1B, 350 °C, 3.5 s			
Soldeerability		"IEC 60068-2-20", Part 2, Test Ta, method 1			
	9.10		4.30 25.95		
	34.90 	5.00 +		-#Ø0.80	
Winding data a		for 12 pipe	EP35/10/11 coil f		
Winding data a		for 12-pins	ER35/19/11 coil f		
Winding data a NUMBER OF SECTIONS			1 AVERAGE	AREA	TYPE NUMBER
NUMBER OF	and area product WINDING AREA	for 12-pins MINIMUM WINDING WIDTH	AVERAGE LENGTH OF TURN	AREA PRODUCT Ae x Aw	TYPE NUMBER ER-3509-1-1S-12P
NUMBER OF SECTIONS 1 Tolerances unless of 0 <l≤4±0.10 4<ls<br="">16<l≤45±0.30 45<="" td=""><td>and area product WINDING AREA (mm²) 120 otherwise specified: <16±0.20 5≤L±0.40</td><td>for 12-pins MINIMUM WINDING WIDTH (mm) 23.80</td><td>AVERAGE LENGTH OF TURN (mm) 61</td><td>AREA PRODUCT Ae x Aw (mm⁴) 12000 RE</td><td>ER-3509-1-1S-12P MARK Bobbin material: T378J</td></l≤45±0.30></l≤4±0.10>	and area product WINDING AREA (mm ²) 120 otherwise specified: <16±0.20 5≤L±0.40	for 12-pins MINIMUM WINDING WIDTH (mm) 23.80	AVERAGE LENGTH OF TURN (mm) 61	AREA PRODUCT Ae x Aw (mm ⁴) 12000 RE	ER-3509-1-1S-12P MARK Bobbin material: T378J
NUMBER OF SECTIONS 1 Tolerances unless of 0 <l≤4±0.10 4<ls<br="">16<l≤45±0.30 45<="" td=""><td>and area product WINDING AREA (mm²) 120 otherwise specified: <16±0.20</td><td>for 12-pins MINIMUM WINDING WIDTH (mm) 23.80</td><td>AVERAGE LENGTH OF TURN (mm) 61</td><td>AREA PRODUCT Ae x Aw (mm⁴) 12000 RE 0:: ER3509-1 .: FAY01091</td><td>ER-3509-1-1S-12P MARK Bobbin material: T378J Available for Fuan core: ER35/19/1</td></l≤45±0.30></l≤4±0.10>	and area product WINDING AREA (mm ²) 120 otherwise specified: <16±0.20	for 12-pins MINIMUM WINDING WIDTH (mm) 23.80	AVERAGE LENGTH OF TURN (mm) 61	AREA PRODUCT Ae x Aw (mm ⁴) 12000 RE 0:: ER3509-1 .: FAY01091	ER-3509-1-1S-12P MARK Bobbin material: T378J Available for Fuan core: ER35/19/1
NUMBER OF SECTIONS 1 Tolerances unless of 0 <l≤4±0.10 4<ls<br="">16<l≤45±0.30 45<br="">Pin Dim:±0.05 Thio</l≤45±0.30></l≤4±0.10>	and area product WINDING AREA (mm ²) 120	for 12-pins MINIMUM WINDING WIDTH (mm) 23.80	AVERAGE LENGTH OF TURN (mm) 61	AREA PRODUCT Ae x Aw (mm ⁴) 12000 RE	ER-3509-1-1S-12P MARK Bobbin material: T378J
NUMBER OF SECTIONS 1 Tolerances unless of 0 <l≤4±0.10 4<ls<br="">16<l≤45±0.30 45<br="">Pin Dim:±0.05 Thio</l≤45±0.30></l≤4±0.10>	and area product WINDING AREA (mm ²) 120 otherwise specified: <16±0.20 5≤L±0.40	for 12-pins MINIMUM WINDING WIDTH (mm) 23.80	AVERAGE LENGTH OF TURN (mm) 61	AREA PRODUCT Ae x Aw (mm ⁴) 12000 RE 0:: ER3509-1 .: FAY01091	ER-3509-1-1S-12P MARK Bobbin material: T378J Available for Fuan core: ER35/19/1

COIL FORMER General data 12-pins ER35/19/11 coil former