


P/N: FALCH4W1008-181K




Outline Dimensions(Unit:mm)




Orthographic view



Top view



Stereogram




Bottom view

Material list

| Part Name | SPEC | Material Type | Supplier | UL Number |
|-------------|-------------------------|---------------|--|-----------|
| Core | DR4W10*8 (S)RCH (B=5.0) | NiZn | FengYin Electronics Corporation or Equivalent supplier | N/A |
| Copper Wire | 2UEW-F | 155°C | Elektrisola Hangzhou Co Ltd | E258243 |

Electrical Schematic



Electrical Characteristics(@25°C)

| Inductance 1KHz,0.1V 1-3 | DC Resistor 1-3 | Rated Current |
|--------------------------------|--------------------|---------------|
| 180uH±10% | 0.350Ω Max | 1.10A |

***Operating Temperature: -40°C~+125°C.
(Temperature rise included)
***Storage Temperature : -40°C~+125°C.
***Storage Humidity:RH10%~70%.

Recommended Soldering Temperature Graph.



| | Standard Profile | Standard Profile |
|------------------|---------------------|---------------------|
| Pre-heating | 150~180°C,90s±30s | |
| Heating | above 220°C,30s-60s | above 240°C,30s Max |
| Peak temperature | 245°C±3°C | 260°C,10s |
| Cycle of reflow | 2 times | |

| | | | | | | | | |
|-----|-------------|------|------|---|---|---|--|--|
| | | | | Tianchang Fuan Electronic Co Ltd www.fuantronics.net TEL: +86-550-7814888 FAX: +86-550-7831133 | Tolerances unless otherwise specified: (.X)±0.50 (.XX)±0.25 Unit of measurement: mm | Make: Qiumei.Liu Checked: Beson. zhan Approved: Anson. zhan | DRAWING TITLE DR4W10*8 RADIAL FILTER CHOKE Material Number: A331008XS150 | Customer Name: Document/Rev: 00 Specification Sheet: 1 of 1 Date of Recognition: Jan./02/2020 |
| REV | DESCRIPTION | APPD | DATE | | | | | |