General data 6-pins UI12.7 coil former PARAMETER **SPECIFICATION** polyamid (PA66), glass reinforced, flame retardant in accordance with "UL 94HB"; Coil former material UL file number E41938 copper-tin alloy (CuSn), tin (Sn) plated Pin material Maximum operating temperature 130°C, "IEC 60085", class B Resistance to soldering heat "IEC 60068-2-20", Part 2, Test Tb, method 1B, 350 °C, 3.5 s Soldeerability "IEC 60068-2-20", Part 2, Test Ta, method 1 12.90 7.20 6.80 6.30 R1.20 0.50 0.40 5.40 0.60 2.80 + 6.30 4.00 11.00 Ŧ 1.7850 -1.86 Ø0.70 4.90 -0 O 0 10.00 -0 0 Q 10.00 C1.0 Winding data and area product for 6-pins UI12.7 coil former MINIMUM AVERAGE AREA WINDING WINDING PRODUCT LENGTH OF NUMBER OF AREA TYPE NUMBER WIDTH TURN SECTIONS Ae x Aw (mm^2) (mm^4) (mm) (mm) 1 20 2*2.85 35 250 UI-12.7-2-2S-6P Dimensions: REMARK Tolerances unless otherwise specified: (mm) Mould No.: UI12.7 Bobbin material: PA66(black) \bigcirc Pin Dim:±0.05 Thickness:±0.20 Pin Pitch:±0.20 Code No.: FAY01091 Available for Fuan core: UI12.7 Make: P.Xiao Material Number: A4E127200100 **Fuan Electronics** TEL :0086-514-87693589 PAIRUI Checked: Beson. zhan Document/Rev: 00 EML :sales@fuantronics.net Approved: Anson. zhan Date of Recognition: Oct./23/2019 WEB:www.fuantronics.net

COIL FORMER