



附注:

1. 未注圆角为R0.05-0.2mm;
2. 端子拉力: 1.1KG Mi n;
3. 最大毛边允许0.05mm;
4. 端子平面度: 0.1mmMax;
5. 产品符合RoHS环保要求;
6. 与上盖SMD-EE-0803C 配合不得过松。

Code No.: FAY 01019

REMARK:			REV.	REVISIONS REC.	DATE:
1.			1.		
2.			2.		
DRAWN BY	Yuing.yu	TOLERANCES 0<L<4 ±0.10 4<L<16 ±0.20 16<L<63 ±0.30 Pin pitch: ±0.2 Wall thickness: ±0.15	ANGLE:	MODEL NAME:	
CHECKED BY	Yong.zhan		±1°	EE8.8(4+4P)-1S	
APPROVED BY	Xueliang.zhan		UNIT:	BOBBIN MATERIAL:	UL REC.
			MM	PM9630	UL 94V-0
			SCALE:	PIN MATERIAL:	REV.
			2:1	CP WIRE	0
 天长市富安电子有限公司 TIAN CHANG FUAN ELECTRONIC CO.,LTD TEL:+86-550-7814888 FAX:+86-550-7831133 Http: www.fuantronics.net				DRAWING NO:	DATE:
				SMD-EE-0803	2018.12.10