



附注:

- 1.未注圆角为R0.05-0.2mm;
- 2.端子拉力: 1.4KG Min;
- 3.最大毛边允许0.05mm;
- 4.端子平面度: 0.1mm Max;
- 5.产品符合RoHS环保要求;
- 6.端子硬度为全硬 190°-210°

Code No.: FAY 01019

REMARK:		REV.	REVISIONS REC.	DATE:
1.		1.	原FAY01025更改为FAY01019(高度增加)。	2018.12.10
2.		2.		
DRAWN BY	Yuing.yu	TOLERANCES		ANGLE: ±1°
CHECKED BY	Yong.zhan	0<L<4 ±0.10 4<L<16 ±0.20 16<L<63 ±0.30 Pin pitch: ±0.2 Wall thickness: ±0.15		MODEL NAME: EP5(4+4P)-1S
APPROVED BY	Xueliang.zhan	UNIT: MM	BOBBIN MATERIAL: PM9630	UL REC. UL 94V-0
 天长市富安电子有限公司 TIAN CHANG FU AN ELECTRONIC CO.,LTD TEL:+86-550-7814888 FAX:+86-550-7831133 Http: www.fuantronics.net		SCALE: 2:1	PIN MATERIAL: C5191	REV. 1
				DRAWING NO: SMD-EP-0501