



附注:

1. 未标注R角0.2mm;
2. 电镀要求:
镍层50-100uIN,
锡层200-500uIN;
3. 最大毛边允许0.1mm;
4. 产品符合RoHS环保要求;
5. 端子平面度: 0.10mm;
6. 端子拉力: 1.5KG Min

Code No.: **FAY 01091**

REMARK:			REV.	REVISIONS REC.	DATE:
1.			1.		
2.			2.		
DRAWN BY	Yuing.yu	TOLERANCES 0<L<4 ±0.10 4<L<16 ±0.20 16<L<63 ±0.30 Pin pitch: ±0.2 Wall thickness: ±0.15	ANGLE:	MODEL NAME:	
CHECKED BY	Yong.zhan		±1°	ER12(4+4P)	
APPROVED BY	Xueliang.zhan		UNIT:	BOBBIN MATERIAL:	UL REC.
			MM	PM9630	UL 94V-0
			SCALE:	PIN MATERIAL:	REV.
			2:1	C5191	0
 天长市富安电子有限公司 TIAN CHANG FUAN ELECTRONIC CO.,LTD TEL:+86-550-7814888 FAX:+86-550-7831133 Http: www.fuantronics.net				DRAWING NO:	DATE:
				SMD-ER-1201	2023.04.07