


P/N: FAPE662304H




Outline Dimensions(Unit:mm)



Note:


- 1.Remove Pins 2,4,5,7,11,12,13,14.

Wave Soldering



- Note:
- 1.Never Contact the ceramic with the iron tip;
  - 2.1.0mm tip diameter(max).

Electronical Schematic



Electrical Characteristics


Input 230Vac 50Hz to 1-8 :  
Excitation current(Ix):50mA Max.  
Output: Vo=17.0Vac Typ(No-load).  
VL=15.0Vac±5%(@2400mA).  
Hi-Pot: Pri-Sec:4000VAC/5mA/60Second.

General Properties

Operating Temperature:-25°C to +40°C.  
Storage Temperature:-25°C to +85°C.  
Insulation Class: B.  
Weight: 0.75kg.

REV	DESCRIPTION	APPD	DATE	Tianchang Fuan Electronic Co Ltd www.fuantronics.net TEL: +86-550-7814888 FAX: +86-550-7831133	<p>Tolerances unless otherwise specified: (.X)±0.50 (XX)±0.25 Unit of measurement: mm</p>	Make: Qiumei.Liu Checked: Beson. zhan Approved: Anson. zhan	<b>DRAWING TITLE</b> 36W Encapsulated Transformer For EI66*23,230VAC Input 50/60Hz	Customer Name:
							Material Number: A226623XS030	Document/Rev: 00
								Specification Sheet: 1 of 2
							Date of Recognition: Jan./02/2020	

P/N: FAPE662304H



List of UL Certificate:

No.	Part Name	Mat'l Description	Supplier	UL Number
1	Bobbin	EI66*23/PBT(Black)	Chang Chun Plastics Co Ltd	E59481
2	Case	CASE-EI66*23/PA66(Orange)	Zhejiang Juner New Materials Co Ltd	E204321
3	Copper wire	2UEW-F/155C	Elektrisola Hangzhou Co Ltd	E258243
4	Core	Lamination	Ta Yea Steel Industry Co Ltd	N/A
5	Epoxy	PU552(Black)	Wevo-Chemle Gmbh	E108835
6				



				Tianchang Fuan Electronic Co Ltd www.fuantronics.net TEL: +86-550-7814888 FAX: +86-550-7831133	Tolerances unless otherwise specified: (.X)±0.50 (XX)±0.25 Unit of measurement: mm	Make: Qiumei.Liu	<b>DRAWING TITLE</b> 36W Encapsulated Transformer For EI66*23,230VAC Input 50/60Hz	Customer Name:
REV	DESCRIPTION	APPD	DATE			Checked: Beson. zhan Approved: Anson. zhan		Document/Rev: 00 Specification Sheet: 2 of 2 Date of Recognition: Jan./02/2020