

HIGH CURRENT POWER INDUCTOR FACPT3020 SERIES



FEATURES:

Magnetic shielded structure: excellent resistance to electromagnetic interference.
 Assemblage design, sturdy structure.
 High inductance, high current, low magnetic loss, low ESR, small parasitic capacitance.
 High temperature wire, closed magnetic circuit, ultra low buzz noise.
 Operating temperature: -40°C~ +125°C
 [Including coils temperature rise].

PRODUCT IDENTIFICATION:

CPT 3020 - 100 M
 a b c d

a:Series name

b:Product dimensions

c:Inductance Value[1R0:1.0uH;100;10uH;101:100uH]

d:Inductance Tolerance[K:10%;M:20%;N:30%]






ELECTRICAL CHARACTERISTICS

Part Number	Inductance [uH]±20%	D.C.Resistor[mΩ]		Saturation Current [A]Typical	Temperature Current [A]Typical
		Typical	Max		
FACPT3020-100M	10	1.45	1.70	30.0	25.0

TEST CONDITIONS

1. All data is tested based on 25°C ambient temperature.
2. Inductance measure condition at 100kHz, 0.1V.
3. Saturation current : the actual value of IDC current when the inductance decrease 30% of its initial value.
4. Temperature rise current : the actual value of IDC current when the temperature rise is ΔT 40 [Ta=25°C].
5. Special remind : Circuit design, component placement, PWB size and thickness, cooling system and etc. All will affect the product temperature. Please verify the product temperature in the final application.

TECHNICAL INFORMATION



ELECTRICAL SCHEMATIC & PAD LAYOUT

DIMENSIONS:MM

Part number	A	B	C	D	E	F	G	H	I	J	K	L
FACPT3020	38.0±1.0	32.5±1.0	21.0 Max	5.0±0.5	33.5±1.0	1.5±0.3	4.0±0.3	33.5 REF	5.0 REF	39.0 REF	33.5 REF	2.0 REF